COMPACT PROFILE END DUMP TRUCK

MODEL **DT-7**

6.4 metric tonne ⋅ 7.0 short ton payload — 3.8 m³ ⋅ 5.0 yd³ capacity



FEATURES

- The 5'-0" (1.52 m) wide DUX DT-7 articulated underground four-wheel drive dump truck is easily manoeuvrable in confined areas and well suited for narrow vein mining
- High power to weight ratio assures fast tramming up steep ramps
- Spacious operator compartment is ergonomically designed for maximum visibility and bi-directional tramming, operator can safely control and monitor all machine functions at a glance
- Clean and rapid discharge cycles guaranteed with 70° dumping angle and smooth flow, wear resistant alloy steel dump box prolongs service life
- Centralized service points and modular design allow for fast service access and quick repair
- Excellent service and parts back-up worldwide

WEIGHTS

Payload	6.4 tonnes	7.0 tons
Machine weight (operating)	7.6 tonnes	8.4 tons
GVW	14.0 tonnes	15.4 tons

SAE VOLUME

Struck	3.4 m³	4.4 yd ³
Heaped	3.8 m³	5.0 yd ³
Custom box size to suit different ore weig	ght available.	•

OVERALL DIMENSIONS

Height over canopy 2	2 085 mm	6′ 10″
Height over box sides 1	805 mm	5′ 11″
Width	l 525 mm	5′ 0″
Length6	3 275 mm	20′ 7″

TURNING RADIUS

Inside	2 745 mm	9' 0"
Outside	4 625 mm	15′ 2″
Angle	45°	

DISCHARGING

ŀ	Height a	at maxim	um dum	o angle 3	125 mm	10′	3"
ľ	Maximu	um dump	angle		70°		

