



NARROW LOW PROFILE END DUMP TRUCK

MODEL DT-26N

26 metric tonne · 28.6 short ton payload — 14.5 m³ · 19.0 yd³ capacity



FEATURES

- Field-proven, articulated DUX DT-26N underground 4-wheel drive dump truck is well suited for hauling ore, waste and backfill on level and steep grades
- Excellent load retention and fast tramming up steep ramps guaranteed — highest power to weight ratio in its class
- Permits efficient chute, side and end loading in narrow drifts with low headings
- Clean and rapid discharge cycles guaranteed with 65° dump angle and smooth flow, wear resistant alloy steel dump box
- Electronically controlled engine reduces fuel consumption and ventilation requirement
- Equipped with 4-wheel POSI-STOP brake system for maximum safety, reliability and low maintenance cost
- Centralized service points and modular design for easy service access and fast component exchange
- Excellent service and parts back-up worldwide

WEIGHTS

Payload 26.0 tonne.....28.6 ton
Machine weight, approx..... 22.7 tonne.....25.0 ton
GVW 48.7 tonne..... 53.6 ton

SAE VOLUME

Struck 12.5 m³..... 16.4 yd³
Heaped 14.5 m³..... 19.0 yd³
Loose ore density.....1.8 t/m³..... 3,034 lb/yd³
Custom box size to suit different ore weight available.

OVERALL DIMENSIONS WITH OPTIONAL TAILGATE

Length..... 10 260 mm.....33' 8"
Width..... 2 285 mm.....7' 6"
Height over box sides..... 2 365 mm.....7' 9"
Height over canopy or cab 2 490 mm.....8' 2"

TURNING RADIUS

Inside.....5 080 mm..... 16' 8"
Outside..... 8 355 mm.....27' 5"
Angle43°

DISCHARGING

Height at maximum dump angle...5 485 mm..... 18' 0"
Maximum dump angle65°



Optional fully-equipped cab.